

US LUBE METAX T18 (Hydro-treated)

Product Description:

Today's technology trend of diesel engine is towards more environment conscious products with less gas emission and longer overhaul period. Coming along with these development, new devices like the Exhaust Gas Recirculation(EGR) rely much more on the performance of the engine oil being used. US Lube Mexta T18 diesel engine oil, the newest product of the United series high performance heavy diesel engine oils, is well positioned to address those needs.

Blended from hydrocracked base stocks and a state-of-art additive package, US Lube Metax T18 diesel engine oil is truly a universal lubricant required for EPA 2007 compliant diesel engines equipped with after treatment devices such as diesel oxidation catalysts and particulate filters. It also meets the latest European ACEA standards and American API performance. This means US Lube Metax T18 diesel engine oil is simply the top player for both the modern North American engines and the top-tier European engines.

Applications / Benefits:

- Provide unsurpassed control of soot.
- Protection of highly stressed piston rings and cylinder liners.
- Exceptional protection of valve train system used in modern diesel system.
- Satisfying most diesel engine OEM oil demand.
- Exceeds the highest API gasoline engine performance as well.
- Particular suitable for the latest diesel engine meeting EURO IV, EURO V and EURO VI emission requirements.

Typical Characteristics:

THE AMEDICAN TECHNOLOGY			
Method	LECIL	IOLOG	I
SAE J 300	10W30	15W40	
ASTM D 4052	0.864	0.882	
ASTM D 92	214	220	
ASTM D 97	-30	-27	
ASTM D 445	78.5	116.6	
ASTM D 445	11.6	14.9	
ASTM D 2270	140	132	
ASTM D 2896	9.5	9.5	
ASTM D 1500	<3.0	<3.0	
	SAE J 300 ASTM D 4052 ASTM D 92 ASTM D 97 ASTM D 445 ASTM D 445 ASTM D 2270 ASTM D 2896	SAE J 300 10W30 ASTM D 4052 0.864 ASTM D 92 214 ASTM D 97 -30 ASTM D 445 78.5 ASTM D 445 11.6 ASTM D 2270 140 ASTM D 2896 9.5	SAE J 300 10W30 15W40 ASTM D 4052 0.864 0.882 ASTM D 92 214 220 ASTM D 97 -30 -27 ASTM D 445 78.5 116.6 ASTM D 445 11.6 14.9 ASTM D 2270 140 132 ASTM D 2896 9.5 9.5

Furnishing the information contained herein does not constitute a representation by US Lube that any product or process is free from patent infringement claims of any third party nor does it constitute the granting of a license under any patent of US Lube or any third party. US Lube assumes no liability for any infringement which might arise out of the product. The information and suggestions for use and application presented herein represent the best information available to us and believed to be reliable. They should not, however, be construed as controlling suggestions, and users urged to conduct confirmatory test to determine final suitability for their specific end uses. US Lube warranty only that its products meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTS relating to the products and the application thereof. EXPRESS or IMPLIED including but not limited to warranties by MERCHANTABLITY and FITNESS.



Specifications, Approvals & Recommendations:

- API CJ-4/CI-4 Plus/CI-4/CH-4/SN/SM
- API CJ-4/CF/SL
- MB-Approval 228.31
- ACEA E7
- ACEA E9
- Cummins CES 20081 & CES 20077, 76, 71
- Volvo VDS-4, VDS-3
- RVI RDL-3
- Detroit Diesel DDC 93K218, 93K215
- Caterpillar ECF-3
- · Caterpillar ECF-2
- Caterpillar ECF-1A
- MAN M3275
- Mack EO-O Premium Plus, Mack EO-M Plus



THE AMERICAN TECHNOLOGY